HUSKEY Specialty Lubricants

manufactured by HUSK-ITT Corporation / SPECIALTY LUBRICANTS Corporation

Western Region Office:
1580 Industrial Avenue, Norco, California 92860
(951) 340-4000 · Fax: (951) 340-4011
(888) 4-HUSKEY · www.huskey.com

Eastern Region Office:
8300 Corporate Park Drive, Macedonia, Ohio 44056
(330) 425-2567 · Fax: (330) 425-9637
(800) 238-LUBE

MATERIAL SAFETY DATA SHEET
CHEMTREC (800) 424-9300 (24HR)

PRODUCT TRADE NAME: HUSKEY CODE 2 PRODUCT CODE 00700

EFFECTIVE DATE: JANUARY 1, 2008

THIS MATERIAL SAFETY DATA SHEET CONTAINS ENVIRONMENTAL, HEALTH AND TOXICOLOGY INFORMATION FOR YOUR EMPLOYEES. PLEASE MAKE SURE THIS INFORMATION IS GIVEN TO THEM. IT ALSO CONTAINS INFORMATION TO HELP YOU MEET COMMUNITY RIGHT-TO-KNOW/EMERGENCY RESPONSE REPORTING REQUIREMENTS UNDER SARA TITLE 111 AND MANY OTHER LAWS. IF YOU RESELL THIS PRODUCT, THIS MSDS MUST BE GIVEN TO THE BUYER OR THE INFORMATION INCORPORATED IN YOUR MSDS.

DOT HAZARDOUS CLASSIFICATION: NOT REGULATED GREASE OR OIL - N.O.S.

NFPA HEALTH HAZARD: 1 FLAMMABILITY: 1 REACTIVITY: 1 PERSONAL PROTECTION: B

SECTION 01- HAZARDOUS INGREDIENTS

IF PRESENT, IARL, NTP AND OSHA CARCINOGENS AND CHEMICAL SUBJECT TO THIS REPORTING REQUIREMENTS OF SARA TITLE 111. SECTION 313 ARE IDENTIFIED IN THIS SECTION.

	CAS NUMBER	TLV	PEL	%
(NON HAZARDOUS) COMPONENTS				
U.S.P. MINERAL OIL	8042-47-5			80 to 90
PROPRIETARY COMPONENTS	**N.J.T.S.R.N.**			
THICKENER	PENDING			6 to 10
ADDITIVES	PENDING			2 to 4

SECTION 02-PHYSICAL DATA

WATER SOLUBILITY.....	INSOLUBLE
SP, GRAVITY, g/ml	0.94
COLOR...	WHITE SEMI-SOLID
APPEARANCE.	MILD PETROLEUM ODOR
EVAPORATION RATE	N/A
BOILING POINT, FE.....	N/A
MELTING POINT, FE.....	N/A
VOLATILE BY VOLUME,%....	N/A
VAPOR PRESSURE...	N/A

SECTION 03-FIRE AND EXPLOSION HAZARDS

FLASH POINT:(ASTM 092) C.O.C. 350EF UPPER FLAMMABLE LIMIT: N/D LOWER FLAMMABLE LIMIT: N/D

EXTINGUISHING MEDIA: DRY CHEMICAL, CARBON DIOXIDE, FOAM, WATER FOG
SPECIAL FIRE FIGHTING PROCEDURES: TREAT AS OIL FIRE; USE SELF-CONTAINED BREATHING APPARATUS.
UNUSUAL FIRE & EXPLOSIVE HAZARDS: NONE

SECTION 04-ENVIRONMENTAL AND DISPOSAL INFORMATION

ACTION TO BE TAKEN FOR SPILL/LEAKS: Stop flow, scrape, wipe, mop up, or absorb with diatomaceous earth or other inert material. Store in appropriate container for disposal.

DISPOSAL METHOD: Disposal should be in compliance with federal, state, and local laws.

SECTION 05-HEALTH HAZARD DATA

CARCINOGENS: No carcinogens present
ROUTE OF ENTRY: Ingestion
EFFECTS OF OVEREXPOSURE: May cause irritation to eyes and skin on sensitive individuals

EMERGENCY FIRST AID PROCEDURES:
EYES: Flush with water for at least 15 minutes
SKIN: Wash with soap and water. See physician if irritation persists.
INHALATION: Remove to fresh air. See physician if irritation persists.
ORAL: Call a physician. Do not induce vomiting. Keep Warm.
ADDITIONAL: Prolonged or repeated contact may produce mild skin irritation and inflammation. Personnel with pre-existing skin disorder should avoid contact.

SECTION 06-REACTIVITY DATA

STABILITY: Stable
INCOMPATIBILITY: Strong oxidizing agents, welding
POLYMERIZATION: Will not occur
THERMAL DECOMPOSITION: Carbon Monoxide. Carbon Dioxide. Trace Metal Oxide
CONDITIONS TO AVOID: Welding

SECTION 07-SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION: Normally not needed

GLOVES PROTECTION: Neoprene or nitrile rubber gloves recommended.

EYE PROTECTION: Approved safety glasses or goggles

OTHER PROTECTION: Chemically resistant boots and apron recommended

WORK/HYGIENIC PRACTICES: Use standard methods

SECTION 08-SPECIAL PRECAUTIONS AND ADDITIONAL INFORMATION

Avoid storage near open flame or other sources of ignition. Spills may cause slippery floors. Proper footwear required. Remove contaminated clothing and launder before reuse. Wash hands with soap and water before eating, drinking or smoking. Discard contaminated leather gloves and shoes.

The above information is based on the data of which we are aware and believed to be correct as of the date hereof. Since the information contained herein may be applied under conditions beyond our control and with which we may be unfamiliar and since data made available subsequent to the date hereof may suggest modification of the information, we do not assume any responsibility for the results of its use. This information is furnished upon condition that the person receiving it shall make his/her own determination of the suitability of the material for his/her particular purpose.

May be used to comply with OSHA'S Hazard Communication Standard 29 CFR 1910.1200. Standard must be consulted for specific requirements.

N/D - Not Determined
< - Less Than
N/A - Not Applicable
> - Greater Than

HUSKEY Specialty Lubricants

manufactured by HUSK-ITT Corporation / SPECIALTY LUBRICANTS Corporation

Western Region Office:
1580 Industrial Avenue, Norco, California 92860
(951) 340-4000 · Fax: (951) 340-4011
(888) 4-HUSKEY · www.huskey.com

Eastern Region Office:
8300 Corporate Park Drive, Macedonia, Ohio 44056
(330) 425-2567 · Fax: (330) 425-9637
(800) 238-LUBE

TECHNICAL REFERENCE INFORMATION

The following *"HUSKEY"* brand lubricants are approved by, or comply with, the outlined regulations and standards.

***HUSKEY* OILS**	***HUSKEY* GREASES**	
FG-300 SERIES	775 FMG	LVI-50
15A14 SERIES	LUBE "O" SEAL	HTL-500
HI-LO SERIES	HVS-100 SILICONE	350 SILICONE
	CODE 2 E.P. FOOD MACHINERY	
	HYDROLUBE	FG-1800 ANTI-SEIZE
	PF-30 LUBE	PF-27 LUBE

F.D.A. APPROVALS:
All components in these products are approved under **FDA** regulation 21 **CFR** paragraph 178.3570 (Lubricants for Incidental Food Contact) as well as other specific regulations.

NSF INTERNATIONAL APPROVALS:
All of the above products are NSF Registered H-1 and approved for incidental food contact (Individual letters available on request).
All components in each of these products meet the NSF standard 61 requirements for drinking water system components but are not Certified by NSF.

U.S.D.A. APPROVALS:
All of the above products are U.S.D.A. H-1 Rated and approved for incidental food contact.
(Individual letters available on request)

KOSHER APPROVAL:
Certified Kosher under the Kashrut supervision of the Rabbinical Council of California.
(Individual letters upon request).
NOTE: *HUSKEY* CODE 2 E.P. FOOD MACHINERY AND HYDROLUBE GREASES ARE NOT APPROVED.

HAZARDOUS COMPONENTS:
All components in these products are non-hazardous per **OSHA** standard 29 **CFR 1900.1200.**
Toxic Substance Control Act (TSCA) – All components in these products are listed on the TSCA Inventory.

For further assistance, contact *HUSK-ITT CORPORATION* at **1-888-4- *HUSKEY*.**